



RENOVATION FLOOR & STAIRS



**REINFORCED PROTECTION
CERAMIC TECHNOLOGY**

SIZES: 750ml – 2L




HIGH PERFORMANCE FOR YOUR DECORATION

RENOVATION FLOOR & STAIRS has been specially developed to renovate high traffic areas like wooden floors, tiled floors and stairs inside the home. The ceramic technology forms a mesh that strengthens the paint: It is both flexible, to absorb shocks without flaking, and hard to withstand high traffic.




- **2 in 1:** no undercoat.
- High resistance to shocks and abrasion due to frequent traffic.
- Stain resistant.
- Does not flake: follows the wood variations.
- Perfectly adheres to smooth surfaces, such as floor tiles.
- Easy application: perfect finish.
- Ultra washable: easy maintenance, resistant to frequent cleaning.


COLOURCHART – satin aspect



White



Cotton



Soft grey



Loft grey



Anthracite

RENOVATION FLOOR & STAIRS

**NO UNDERCOAT
NO STRIPPING**

Drying time:
Recoat: **3h** Fully dry: **24h**
Tool cleaning: **water**

COVERAGE:
750ml = +/- 8m² - 2L = +/- 20m²

This paint has been specially developed for new or old tiled floors, wooden floors and stairs, made from:

- Wood, already varnished or painted, laminates.
- Tiles : porcelain stoneware, enameled tiles.
- Natural hard stones: marble, granite.

Does not apply to tiled floors in showers or walk-in showers.

TOOLS:

- Paint stirrer or wide stick
- 4-5mm short pile roller (tiled floors)
- 8 to 12mm pile roller (wooden floors)
- Round edged paint brush (for angles, corners & finishes)



PREPARATION:

PREPARATION of the surface is **ESSENTIAL**

WASH the surface with a soda-based or sugar soap (alkaline) cleaner.

- **On laminate and varnished or painted wood in good condition** : wash, rinse and allow to dry. Sand (240 grit) and remove dust.
- **On oak and raw chestnut**: apply a suitable undercoat to block the tannins.
- **On raw tiled floor**: wash, insist on groutings, rinse and allow to dry.
- **On tiled floor already painted in good condition**: wash, rinse thoroughly and allow to dry. Sand (240 grit) and remove dust.
- **On tiled floor already painted or partially worn**: Sand with sandpaper (60 then 120 grit) to return to the original surface. Remove dust, wash, rinse and allow to dry.

APPLICATION:

Apply the paint at room temperature between 12 and 25°C and avoid draughts.

1. Empty the additive (the sachet that is placed under the lid of the pack) into the paint. Stir the paint for 5 minutes, working around the bottom of the tin with a wide stick to mix it well.
2. Start with the edge of the room with the brush and continue with the roller. Work on small surfaces. Apply from one end to the other. Follow with successive cross strokes. Do not start 2nd coat while it's still drying. Leave to dry for 3h and apply a 2nd coat in the same way. A 3rd coat may be required depending on the surface and colour.

Once the sachet has been added, the mixture must be used within 10 days to maintain optimal adhesion and performance.

V33 TIPS:

To clean your painted surfaces, use a gentle detergent and a mop.

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application..

HEALTH AND SAFETY

EUH208: Contains 1,2-benzisothiazol-3(2H)-one; reaction mass of : 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May cause an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. EU limit value for this product (cat A/j) : 140g/L (2010). This product contains max 33g/L VOC.

